

## Circumferinta roti bicicleta pentru setare ciclocomputer

<b>Roata</b>	<b>Janta ISO</b>	<b>Cauciuc</b>	<b>Cauciuc mm</b>	<b>Diametru</b>	<b>Circumferinta</b>
27inch	630	20 mm	20	670	<b>2104.87</b>
27inch	630	23 mm	23	676	<b>2123.72</b>
27inch	630	25 mm	25	680	<b>2136.28</b>
27inch	630	28 mm	28	686	<b>2155.13</b>
27inch	630	32 mm	32	694	<b>2180.27</b>
27inch	630	35 mm	35	700	<b>2199.11</b>
27inch	630	38 mm	38	706	<b>2217.96</b>
27inch	630	44 mm	44	718	<b>2255.66</b>
27inch	630	50 mm	50	730	<b>2293.36</b>
27inch	630	56 mm	56	742	<b>2331.06</b>
27inch	630	1.00 inch	25.4	680.8	<b>2138.8</b>
27inch	630	1.25 inch	31.75	693.5	<b>2178.69</b>
27inch	630	1.5 inch	38.1	706.2	<b>2218.59</b>
27inch	630	1.75 inch	44.45	718.9	<b>2258.49</b>
27inch	630	1.90 inch	48.26	726.52	<b>2282.43</b>
27inch	630	1.95 inch	49.5	729	<b>2290.22</b>
27inch	630	2.00 inch	50.8	731.6	<b>2298.39</b>
27inch	630	2.10 inch	53.34	736.68	<b>2314.35</b>
27inch	630	2.125 inch	54	738	<b>2318.5</b>
27inch	630	2.20 inch	55.88	741.76	<b>2330.31</b>
27inch	630	2.25 inch	57.15	744.3	<b>2338.29</b>
27inch	630	2.30 inch	58.42	746.84	<b>2346.27</b>
27inch	630	2.35 inch	59.69	749.38	<b>2354.25</b>
27inch	630	2.40 inch	60.69	751.38	<b>2360.53</b>
700c/29er/28	622	20 mm	20	662	<b>2079.73</b>
700c/29er/28	622	23 mm	23	668	<b>2098.58</b>
700c/29er/28	622	25 mm	25	672	<b>2111.15</b>
700c/29er/28	622	28 mm	28	678	<b>2130</b>
700c/29er/28	622	32 mm	32	686	<b>2155.13</b>
700c/29er/28	622	35 mm	35	692	<b>2173.98</b>
700c/29er/28	622	38 mm	38	698	<b>2192.83</b>
700c/29er/28	622	44 mm	44	710	<b>2230.53</b>
700c/29er/28	622	50 mm	50	722	<b>2268.23</b>
700c/29er/28	622	56 mm	56	734	<b>2305.93</b>
700c/29er/28	622	1.00 inch	25.4	672.8	<b>2113.66</b>
700c/29er/28	622	1.25 inch	31.75	685.5	<b>2153.56</b>
700c/29er/28	622	1.5 inch	38.1	698.2	<b>2193.46</b>
700c/29er/28	622	1.75 inch	44.45	710.9	<b>2233.36</b>
700c/29er/28	622	1.90 inch	48.26	718.52	<b>2257.3</b>
700c/29er/28	622	1.95 inch	49.5	721	<b>2265.09</b>
700c/29er/28	622	2.00 inch	50.8	723.6	<b>2273.26</b>
700c/29er/28	622	2.10 inch	53.34	728.68	<b>2289.22</b>
700c/29er/28	622	2.125 inch	54	730	<b>2293.36</b>
700c/29er/28	622	2.20 inch	55.88	733.76	<b>2305.18</b>
700c/29er/28	622	2.25 inch	57.15	736.3	<b>2313.15</b>
700c/29er/28	622	2.30 inch	58.42	738.84	<b>2321.13</b>

## Circumferinta roti bicicleta pentru setare ciclocomputer

<b>Roata</b>	<b>Janta ISO</b>	<b>Cauciuc</b>	<b>Cauciuc mm</b>	<b>Diametru</b>	<b>Circumferinta</b>
700c/29er/28	622	2.35 inch	59.69	741.38	<b>2329.11</b>
700c/29er/28	622	2.40 inch	60.69	743.38	<b>2335.4</b>
650b/27.5	584	20 mm	20	624	<b>1960.35</b>
650b/27.5	584	23 mm	23	630	<b>1979.2</b>
650b/27.5	584	25 mm	25	634	<b>1991.77</b>
650b/27.5	584	28 mm	28	640	<b>2010.62</b>
650b/27.5	584	32 mm	32	648	<b>2035.75</b>
650b/27.5	584	35 mm	35	654	<b>2054.6</b>
650b/27.5	584	38 mm	38	660	<b>2073.45</b>
650b/27.5	584	44 mm	44	672	<b>2111.15</b>
650b/27.5	584	50 mm	50	684	<b>2148.85</b>
650b/27.5	584	56 mm	56	696	<b>2186.55</b>
650b/27.5	584	1.00 inch	25.4	634.8	<b>1994.28</b>
650b/27.5	584	1.25 inch	31.75	647.5	<b>2034.18</b>
650b/27.5	584	1.5 inch	38.1	660.2	<b>2074.08</b>
650b/27.5	584	1.75 inch	44.45	672.9	<b>2113.98</b>
650b/27.5	584	1.90 inch	48.26	680.52	<b>2137.92</b>
650b/27.5	584	1.95 inch	49.5	683	<b>2145.71</b>
650b/27.5	584	2.00 inch	50.8	685.6	<b>2153.88</b>
650b/27.5	584	2.10 inch	53.34	690.68	<b>2169.84</b>
650b/27.5	584	2.125 inch	54	692	<b>2173.98</b>
650b/27.5	584	2.20 inch	55.88	695.76	<b>2185.79</b>
650b/27.5	584	2.25 inch	57.15	698.3	<b>2193.77</b>
650b/27.5	584	2.30 inch	58.42	700.84	<b>2201.75</b>
650b/27.5	584	2.35 inch	59.69	703.38	<b>2209.73</b>
650b/27.5	584	2.40 inch	60.69	705.38	<b>2216.02</b>
650c	571	20 mm	20	611	<b>1919.51</b>
650c	571	23 mm	23	617	<b>1938.36</b>
650c	571	25 mm	25	621	<b>1950.93</b>
650c	571	28 mm	28	627	<b>1969.78</b>
650c	571	32 mm	32	635	<b>1994.91</b>
650c	571	35 mm	35	641	<b>2013.76</b>
650c	571	38 mm	38	647	<b>2032.61</b>
650c	571	44 mm	44	659	<b>2070.31</b>
650c	571	50 mm	50	671	<b>2108.01</b>
650c	571	56 mm	56	683	<b>2145.71</b>
650c	571	1.00 inch	25.4	621.8	<b>1953.44</b>
650c	571	1.25 inch	31.75	634.5	<b>1993.34</b>
650c	571	1.5 inch	38.1	647.2	<b>2033.24</b>
650c	571	1.75 inch	44.45	659.9	<b>2073.14</b>
650c	571	1.90 inch	48.26	667.52	<b>2097.08</b>
650c	571	1.95 inch	49.5	670	<b>2104.87</b>
650c	571	2.00 inch	50.8	672.6	<b>2113.04</b>
650c	571	2.10 inch	53.34	677.68	<b>2128.99</b>
650c	571	2.125 inch	54	679	<b>2133.14</b>
650c	571	2.20 inch	55.88	682.76	<b>2144.95</b>

### Circumferinta roti bicicleta pentru setare ciclocomputer

<b>Roata</b>	<b>Janta ISO</b>	<b>Cauciuc</b>	<b>Cauciuc mm</b>	<b>Diametru</b>	<b>Circumferinta</b>
650c	571	2.25 inch	57.15	685.3	<b>2152.93</b>
650c	571	2.30 inch	58.42	687.84	<b>2160.91</b>
650c	571	2.35 inch	59.69	690.38	<b>2168.89</b>
650c	571	2.40 inch	60.69	692.38	<b>2175.18</b>
26inch mtb	559	20 mm	20	599	<b>1881.81</b>
26inch mtb	559	23 mm	23	605	<b>1900.66</b>
26inch mtb	559	25 mm	25	609	<b>1913.23</b>
26inch mtb	559	28 mm	28	615	<b>1932.08</b>
26inch mtb	559	32 mm	32	623	<b>1957.21</b>
26inch mtb	559	35 mm	35	629	<b>1976.06</b>
26inch mtb	559	38 mm	38	635	<b>1994.91</b>
26inch mtb	559	44 mm	44	647	<b>2032.61</b>
26inch mtb	559	50 mm	50	659	<b>2070.31</b>
26inch mtb	559	56 mm	56	671	<b>2108.01</b>
26inch mtb	559	1.00 inch	25.4	609.8	<b>1915.74</b>
26inch mtb	559	1.25 inch	31.75	622.5	<b>1955.64</b>
26inch mtb	559	1.5 inch	38.1	635.2	<b>1995.54</b>
26inch mtb	559	1.75 inch	44.45	647.9	<b>2035.44</b>
26inch mtb	559	1.90 inch	48.26	655.52	<b>2059.38</b>
26inch mtb	559	1.95 inch	49.5	658	<b>2067.17</b>
26inch mtb	559	2.00 inch	50.8	660.6	<b>2075.34</b>
26inch mtb	559	2.10 inch	53.34	665.68	<b>2091.3</b>
26inch mtb	559	2.125 inch	54	667	<b>2095.44</b>
26inch mtb	559	2.20 inch	55.88	670.76	<b>2107.25</b>
26inch mtb	559	2.25 inch	57.15	673.3	<b>2115.23</b>
26inch mtb	559	2.30 inch	58.42	675.84	<b>2123.21</b>
26inch mtb	559	2.35 inch	59.69	678.38	<b>2131.19</b>
26inch mtb	559	2.40 inch	60.69	680.38	<b>2137.48</b>
24inch S5	547	20 mm	20	587	<b>1844.11</b>
24inch S5	547	23 mm	23	593	<b>1862.96</b>
24inch S5	547	25 mm	25	597	<b>1875.53</b>
24inch S5	547	28 mm	28	603	<b>1894.38</b>
24inch S5	547	32 mm	32	611	<b>1919.51</b>
24inch S5	547	35 mm	35	617	<b>1938.36</b>
24inch S5	547	38 mm	38	623	<b>1957.21</b>
24inch S5	547	44 mm	44	635	<b>1994.91</b>
24inch S5	547	50 mm	50	647	<b>2032.61</b>
24inch S5	547	56 mm	56	659	<b>2070.31</b>
24inch S5	547	1.00 inch	25.4	597.8	<b>1878.04</b>
24inch S5	547	1.25 inch	31.75	610.5	<b>1917.94</b>
24inch S5	547	1.5 inch	38.1	623.2	<b>1957.84</b>
24inch S5	547	1.75 inch	44.45	635.9	<b>1997.74</b>
24inch S5	547	1.90 inch	48.26	643.52	<b>2021.68</b>
24inch S5	547	1.95 inch	49.5	646	<b>2029.47</b>
24inch S5	547	2.00 inch	50.8	648.6	<b>2037.64</b>
24inch S5	547	2.10 inch	53.34	653.68	<b>2053.6</b>

## Circumferinta roti bicicleta pentru setare ciclocomputer

<b>Roata</b>	<b>Janta ISO</b>	<b>Cauciuc</b>	<b>Cauciuc mm</b>	<b>Diametru</b>	<b>Circumferinta</b>
24inch S5	547	2.125 inch	54	655	<b>2057.74</b>
24inch S5	547	2.20 inch	55.88	658.76	<b>2069.56</b>
24inch S5	547	2.25 inch	57.15	661.3	<b>2077.54</b>
24inch S5	547	2.30 inch	58.42	663.84	<b>2085.51</b>
24inch S5	547	2.35 inch	59.69	666.38	<b>2093.49</b>
24inch S5	547	2.40 inch	60.69	668.38	<b>2099.78</b>
24inch E6	540	20 mm	20	580	<b>1822.12</b>
24inch E6	540	23 mm	23	586	<b>1840.97</b>
24inch E6	540	25 mm	25	590	<b>1853.54</b>
24inch E6	540	28 mm	28	596	<b>1872.39</b>
24inch E6	540	32 mm	32	604	<b>1897.52</b>
24inch E6	540	35 mm	35	610	<b>1916.37</b>
24inch E6	540	38 mm	38	616	<b>1935.22</b>
24inch E6	540	44 mm	44	628	<b>1972.92</b>
24inch E6	540	50 mm	50	640	<b>2010.62</b>
24inch E6	540	56 mm	56	652	<b>2048.32</b>
24inch E6	540	1.00 inch	25.4	590.8	<b>1856.05</b>
24inch E6	540	1.25 inch	31.75	603.5	<b>1895.95</b>
24inch E6	540	1.5 inch	38.1	616.2	<b>1935.85</b>
24inch E6	540	1.75 inch	44.45	628.9	<b>1975.75</b>
24inch E6	540	1.90 inch	48.26	636.52	<b>1999.69</b>
24inch E6	540	1.95 inch	49.5	639	<b>2007.48</b>
24inch E6	540	2.00 inch	50.8	641.6	<b>2015.65</b>
24inch E6	540	2.10 inch	53.34	646.68	<b>2031.61</b>
24inch E6	540	2.125 inch	54	648	<b>2035.75</b>
24inch E6	540	2.20 inch	55.88	651.76	<b>2047.56</b>
24inch E6	540	2.25 inch	57.15	654.3	<b>2055.54</b>
24inch E6	540	2.30 inch	58.42	656.84	<b>2063.52</b>
24inch E6	540	2.35 inch	59.69	659.38	<b>2071.5</b>
24inch E6	540	2.40 inch	60.69	661.38	<b>2077.79</b>
24inch Terry	520	20 mm	20	560	<b>1759.29</b>
24inch Terry	520	23 mm	23	566	<b>1778.14</b>
24inch Terry	520	25 mm	25	570	<b>1790.71</b>
24inch Terry	520	28 mm	28	576	<b>1809.56</b>
24inch Terry	520	32 mm	32	584	<b>1834.69</b>
24inch Terry	520	35 mm	35	590	<b>1853.54</b>
24inch Terry	520	38 mm	38	596	<b>1872.39</b>
24inch Terry	520	44 mm	44	608	<b>1910.09</b>
24inch Terry	520	50 mm	50	620	<b>1947.79</b>
24inch Terry	520	56 mm	56	632	<b>1985.49</b>
24inch Terry	520	1.00 inch	25.4	570.8	<b>1793.22</b>
24inch Terry	520	1.25 inch	31.75	583.5	<b>1833.12</b>
24inch Terry	520	1.5 inch	38.1	596.2	<b>1873.02</b>
24inch Terry	520	1.75 inch	44.45	608.9	<b>1912.92</b>
24inch Terry	520	1.90 inch	48.26	616.52	<b>1936.85</b>
24inch Terry	520	1.95 inch	49.5	619	<b>1944.65</b>

### Circumferinta roti bicicleta pentru setare ciclocomputer

<b>Roata</b>	<b>Janta ISO</b>	<b>Cauciuc</b>	<b>Cauciuc mm</b>	<b>Diametru</b>	<b>Circumferinta</b>
24inch Terry	520	2.00 inch	50.8	621.6	<b>1952.81</b>
24inch Terry	520	2.10 inch	53.34	626.68	<b>1968.77</b>
24inch Terry	520	2.125 inch	54	628	<b>1972.92</b>
24inch Terry	520	2.20 inch	55.88	631.76	<b>1984.73</b>
24inch Terry	520	2.25 inch	57.15	634.3	<b>1992.71</b>
24inch Terry	520	2.30 inch	58.42	636.84	<b>2000.69</b>
24inch Terry	520	2.35 inch	59.69	639.38	<b>2008.67</b>
24inch Terry	520	2.40 inch	60.69	641.38	<b>2014.95</b>
20inch Recumbent	451	20 mm	20	491	<b>1542.52</b>
20inch Recumbent	451	23 mm	23	497	<b>1561.37</b>
20inch Recumbent	451	25 mm	25	501	<b>1573.94</b>
20inch Recumbent	451	28 mm	28	507	<b>1592.79</b>
20inch Recumbent	451	32 mm	32	515	<b>1617.92</b>
20inch Recumbent	451	35 mm	35	521	<b>1636.77</b>
20inch Recumbent	451	38 mm	38	527	<b>1655.62</b>
20inch Recumbent	451	44 mm	44	539	<b>1693.32</b>
20inch Recumbent	451	50 mm	50	551	<b>1731.02</b>
20inch Recumbent	451	56 mm	56	563	<b>1768.72</b>
20inch Recumbent	451	1.00 inch	25.4	501.8	<b>1576.45</b>
20inch Recumbent	451	1.25 inch	31.75	514.5	<b>1616.35</b>
20inch Recumbent	451	1.5 inch	38.1	527.2	<b>1656.25</b>
20inch Recumbent	451	1.75 inch	44.45	539.9	<b>1696.15</b>
20inch Recumbent	451	1.90 inch	48.26	547.52	<b>1720.08</b>
20inch Recumbent	451	1.95 inch	49.5	550	<b>1727.88</b>
20inch Recumbent	451	2.00 inch	50.8	552.6	<b>1736.04</b>
20inch Recumbent	451	2.10 inch	53.34	557.68	<b>1752</b>
20inch Recumbent	451	2.125 inch	54	559	<b>1756.15</b>
20inch Recumbent	451	2.20 inch	55.88	562.76	<b>1767.96</b>
20inch Recumbent	451	2.25 inch	57.15	565.3	<b>1775.94</b>
20inch Recumbent	451	2.30 inch	58.42	567.84	<b>1783.92</b>
20inch Recumbent	451	2.35 inch	59.69	570.38	<b>1791.9</b>
20inch Recumbent	451	2.40 inch	60.69	572.38	<b>1798.18</b>
20inch Schwinn	419	20 mm	20	459	<b>1441.99</b>
20inch Schwinn	419	23 mm	23	465	<b>1460.84</b>
20inch Schwinn	419	25 mm	25	469	<b>1473.41</b>
20inch Schwinn	419	28 mm	28	475	<b>1492.26</b>
20inch Schwinn	419	32 mm	32	483	<b>1517.39</b>
20inch Schwinn	419	35 mm	35	489	<b>1536.24</b>
20inch Schwinn	419	38 mm	38	495	<b>1555.09</b>
20inch Schwinn	419	44 mm	44	507	<b>1592.79</b>
20inch Schwinn	419	50 mm	50	519	<b>1630.49</b>
20inch Schwinn	419	56 mm	56	531	<b>1668.19</b>
20inch Schwinn	419	1.00 inch	25.4	469.8	<b>1475.92</b>
20inch Schwinn	419	1.25 inch	31.75	482.5	<b>1515.82</b>
20inch Schwinn	419	1.5 inch	38.1	495.2	<b>1555.72</b>
20inch Schwinn	419	1.75 inch	44.45	507.9	<b>1595.61</b>

## Circumferinta roti bicicleta pentru setare ciclocomputer

<b>Roata</b>	<b>Janta ISO</b>	<b>Cauciuc</b>	<b>Cauciuc mm</b>	<b>Diametru</b>	<b>Circumferinta</b>
20inch Schwinn	419	1.90 inch	48.26	515.52	<b>1619.55</b>
20inch Schwinn	419	1.95 inch	49.5	518	<b>1627.34</b>
20inch Schwinn	419	2.00 inch	50.8	520.6	<b>1635.51</b>
20inch Schwinn	419	2.10 inch	53.34	525.68	<b>1651.47</b>
20inch Schwinn	419	2.125 inch	54	527	<b>1655.62</b>
20inch Schwinn	419	2.20 inch	55.88	530.76	<b>1667.43</b>
20inch Schwinn	419	2.25 inch	57.15	533.3	<b>1675.41</b>
20inch Schwinn	419	2.30 inch	58.42	535.84	<b>1683.39</b>
20inch Schwinn	419	2.35 inch	59.69	538.38	<b>1691.37</b>
20inch Schwinn	419	2.40 inch	60.69	540.38	<b>1697.65</b>
20inch Recumbent	406	20 mm	20	446	<b>1401.15</b>
20inch Recumbent	406	23 mm	23	452	<b>1420</b>
20inch Recumbent	406	25 mm	25	456	<b>1432.57</b>
20inch Recumbent	406	28 mm	28	462	<b>1451.42</b>
20inch Recumbent	406	32 mm	32	470	<b>1476.55</b>
20inch Recumbent	406	35 mm	35	476	<b>1495.4</b>
20inch Recumbent	406	38 mm	38	482	<b>1514.25</b>
20inch Recumbent	406	44 mm	44	494	<b>1551.95</b>
20inch Recumbent	406	50 mm	50	506	<b>1589.65</b>
20inch Recumbent	406	56 mm	56	518	<b>1627.34</b>
20inch Recumbent	406	1.00 inch	25.4	456.8	<b>1435.08</b>
20inch Recumbent	406	1.25 inch	31.75	469.5	<b>1474.98</b>
20inch Recumbent	406	1.5 inch	38.1	482.2	<b>1514.88</b>
20inch Recumbent	406	1.75 inch	44.45	494.9	<b>1554.77</b>
20inch Recumbent	406	1.90 inch	48.26	502.52	<b>1578.71</b>
20inch Recumbent	406	1.95 inch	49.5	505	<b>1586.5</b>
20inch Recumbent	406	2.00 inch	50.8	507.6	<b>1594.67</b>
20inch Recumbent	406	2.10 inch	53.34	512.68	<b>1610.63</b>
20inch Recumbent	406	2.125 inch	54	514	<b>1614.78</b>
20inch Recumbent	406	2.20 inch	55.88	517.76	<b>1626.59</b>
20inch Recumbent	406	2.25 inch	57.15	520.3	<b>1634.57</b>
20inch Recumbent	406	2.30 inch	58.42	522.84	<b>1642.55</b>